

**VOLGA**  **TIRE**

  
**CAPELLI**



# **CATALOG**

## **TRUCK & BUS RADIAL TIRE**

## Recommended Application

STEERING



DRIVING



OFF ROAD



ALL POSITION




WIDE SINGLE





## CL128




- ◎ Easy handing.
- ◎ Tough belt construction reduces heating and irregular wear.
- ◎ Special tread compound provides longer mileage and minimizes tread injuries.
- ◎ Quiet and smooth riding.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
215/75R17.5	TL	16	127/124	L	767	211	13.5	6.00	1750	1600	830
235/75R17.5	TL	16	132/129	J	797	233	13.5	6.75	2000	1850	830



## CL267




- ◎ Easy handing.
- ◎ Tough belt construction reduces heating and irregular wear.
- ◎ Special tread compound provides longer mileage and minimizes tread injuries.
- ◎ Quiet and smooth riding .

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	16.5	9.00	3550	3250	930



## CL288



- ◎ Three main grooves and two block type ribs on the tread center provide good traction on wet and dry road conditions.
- ◎ Special anti-cut tread compound provides high resistance for cut and chipping.
- ◎ Tough belt construction for smooth tread wear.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
10.00R20	TT	18	149/146	K	1054	278	16.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	16.5	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	16.5	8.5	3750	3450	830



## CL400




- ◎ Easy handing.
- ◎ Tough belt construction reduces heating and irregular wear.
- ◎ Special tread compound provides longer mileage and minimizes tread injuries.
- ◎ Quiet and smooth riding.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
11R22.5	TL	16	146/143	M	1054	279	15.00	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300		9.00	3550	3250	930
13R22.5	TL	18	154/151	L	1124	320	15.00	9.75	3750	3450	830
295/80R22.5	TL	18	152/149	L	1044	298	15.00	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	15.00	9.00	4125	3750	900

STEERING	DRIVING	OFF ROAD	ALL POSITION	WIDE SINGLE
----------	---------	----------	--------------	-------------



## CL400+




- Easy handing.
- Tough belt construction reduces heating and irregular wear.
- Special tread compound provides longer mileage and minimizes tread injuries.
- Quiet and smooth riding.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930



## CL400++




- Adopted "Plus+" concept.
- Added more mileage.
  - widen tread width and revised land/sea ratio.
- Given more stability.
  - widen shoulder and center rib given more road holding.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
11R22.5	TL	16	146/143	M	1054	279	15.0	8.25	3000	2725	830
295/80R22.5	TL	18	152/149	L	1044	298	15.0	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	15.0	9.00	4125	3750	900



## CL150




- 5-rib tread design with special compounds are suit for long haul service.
- Deeper pattern makes tire have longer service life.
- Optimized groove designing guarantees tire wet grip performance.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930



## CL250




- Strong shoulder lugs provides excellent gripping power on muddy road conditions.
- Tough belt construction for smooth tread wear and longer mileage.
- Special tread compound for high resistance against tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
6.50R16LT	TT	12	110/105	L	750	185	12.5	5.50F	975	80	560
7.00R16LT	TT	14	118/114	L	775	200	14.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	K	805	215	14.0	6.00F	1500	1320	770
8.25R16LT	TT	16	128/124	K	855	235	16.5	6.50F	1800	1600	770
8.25R20	TT	16	139/137	K	974	236	17.0	6.5	2430	2300	930
9.00R20	TT	16	144/142	K	1019	259	17.5	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1054	278	18.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	21.5	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	22.0	8.5	3750	3450	830
12.00R24	TT	20	160/157	K	1226	315	22.0	8.5	4500	4125	900



## CL286




- Special pattern design provides good traction and driving capacity.
- Tough belt for smooth tread wear and longer mileage.
- Special compound for high resistance against tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1096	300	21.0	9.00	3550	3250	930



## CL258




- Block tread pattern provides excellent gripping power on both wet and dry road conditions.
- Tough belt construction for smooth wear and longer mileage.
- Special tread compound for high resistance against tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
10.00R20	TT	18	149/146	K	1054	178	16.5	7.5	3250	3000	930
12.00R20	TT	20	156/153	J	1125	315	17.5	8.5	3750	3450	830
11.00R20	TT	18	152/149	K	1085	293	17.5	8.0	3550	3250	930



## CL118



- Lug groove provide more traction.
- Special tread design for mixed road condition.
- Reinforced bead and body to ensure durability.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
215/75R17.5	TL	16	127/124	L	767	211	15.5	6.00	1750	1600	830
235/75R17.5	TL	16	132/129	J	797	233	15.5	6.75	2000	1850	830
6.50R16LT	TT	12	110/105	L	754	185	14.0	5.50F	1060	925	670
7.00R16LT	TT	14	118/114	L	775	200	15.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	K	810	215	15.5	6.00F	1500	1320	770
8.25R16LT	TT	16	128/124	K	853	235	15.5	6.50F	1800	1600	770
8.25R20	TT	16	139/137	K	970	236	16.5	6.50F	2430	2300	930



## CL296




- Adopted convex-shaped blocks for higher gripping power on both wet and dry road conditions.
- Tough belt construction for smooth tread wear and longer mileage.
- Special tread compound for minimizing tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
11R22.5	TL	16	146/143	L	1054	279	18.0	8.25	3000	2725	830
315/80R22.5	TL	20	157/154	L	1076	312	20.5	9.00	4125	3750	900



## CL296+




- Adopted plus+ concept.
- Added more mileage.
- Widen tread width.
- Increased road contact area.
- Increased gripping power.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
295/80R22.5	TL	18	152/149	L	1044	298	18.0	9.00	3550	3250	900
12R22.5	TL	18	152/149	L	1085	300	20.5	9.00	3550	3250	930



## CL277




- Block tread design provide strongtraction and breaking power.
- Tough belt construction for smooth wear and longer mileage.
- Reinforced bead and body to ensure durability.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
315/80R22.5	TL	20	157/154	L	1076	312	22.0	9.00	4125	3750	900



## CL297



- Block tread design provide strongtraction and breaking power.
- Tough belt construction for smooth wear and longer mileage.
- Reinforced bead and body to ensure durability.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
315/80R22.5	TT	20	157/154	L	1076	312	19.5	9.00	4125	3750	900



## CL299




- Opened shoulder and blocks on the tread center provide high traction power on both wet and dry road conditions.
- Tough belt construction for smooth tread wear and longer mileage.
- Special tread compound for minimizing tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
11R22.5	TL	16	146/143	L	1054	279	18.0	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	18.0	9.00	3550	3250	930
295/80R22.5	TL	18	152/149	L	1044	298	20.0	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	20.0	9.00	4125	3750	900



## CL318




- Zigzag block provide excellent traction and braking power.
- Special compound and waterproof and anti-puncturing construction.
- Reinforced bead and body construction improve durability.
- Tough tread blocks for high traction on the muddy road.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
13R22.5	TL	18	154/151	L	1136	320	20.0	9.75	3750	3450	830
11.00R20	TT	18	152/149	K	1085	293	20.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	20.0	8.5	3750	3450	830



## CL368



- Big block provide strong traction and braking power.
- Open groove and bottom design given very good self-cleaning performance.
- Open shoulder reduce heat.
- Reinforced bead and body to ensure durability.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
8.25R16LT	TT	16	128/124	K	855	235	15.5	6.50H	1800	1600	770
9.00R20	TT	16	144/142	K	1019	259	18.0	7.0	2800	2650	900
11.00R20	TT	18	152/149	K	1085	293	19.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	21.0	8.5	3750	3450	830



## YB398



- Block tread design provide strong traction and breaking power.
- Tough belt construction for smooth wear and longer mileage.
- Reinforced bead and body to ensure durability.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12.00R20	TT	20	156/153	J	1126	315	21.0	8.5	3750	3450	830



## YB866




- Special pattern design provides good traction and driving capacity.
- Tough belt for smooth tread wear and longer mileage.
- Special compound for high resistance against tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
10.00R20	TT	18	149/146	K	1054	278	18.5	7.5	3250	3000	930



## CL900




- Special pattern design provides good traction and driving capacity.
- Special rib and lug mixed pattern for smooth tread wear.
- High safety and re-capping capacity.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
9.00R20	TT	16	144/142	K	1019	259	18.0	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1054	278	18.5	7.5	3250	3000	930



## CL918




- Special pattern design provides good traction and driving capacity.
- Tough belt for smooth tread wear and longer mileage.
- Special compound for high resistance against tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1087	300	18.0	9.00	3550	3250	930



## CL170




- Wider tread and deeper pattern makes tire more excellent abrasion resistance and longer service life.
- Unidirectional pattern and unique block designing provide excellent driving and wet grip performance.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	21.0	9.00	3550	3250	930



## CL180




- Special tread pattern design, higher traction on mining road.
- Extra deep pattern, longer service life.
- Unique groove design, higher ability of self-clean without derit into it completely.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	21.0	9.00	3550	3250	930



## CL198




- Special tread design for city bus.
- Cool-Wind decoration on the sidewall.
- Special tread compound for cut protection and reducing heating.
- Tough belt construction for smooth tread wear.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
275/70R22.5	TL	16	144/141	J	964	276	22.5	8.25	2800	2575	830



## CL218




- Wide tread design to extend tire service life.
- Low rolling resistance and excellent heat dispersion performance.
- Wide shoulder provide excellent road holding.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930



## CL268



- Shoulder lugs for more traction and center ribs are for stable handing.
- Tough belt for smooth wear and longer mileage.
- Special tread compound for high resistance tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
6.50R16LT	TT	12	110/105	L	750	185	10.5	5.50F	975	850	560
7.00R16LT	TT	14	118/114	L	775	200	12.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	K	805	215	13.0	6.00F	1500	1320	770
8.25R16LT	TT	16	128/124	K	855	235	14.5	6.50F	1800	1600	770
8.25R20	TT	16	139/137	K	974	236	15.0	6.5	2430	2300	930
9.00R20	TT	16	144/142	K	1019	259	15.5	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1054	278	16.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	17.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	17.5	8.5	3750	3450	830
12.00R24	TT	20	160/157	K	1226	315	17.5	8.5	4500	4125	900
11R22.5	TL	16	146/143	M	1054	279	17.5	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930
13R22.5	TL	18	154/151	L	1136	320	18.0	9.75	3750	3450	830
315/80R22.5	TL	20	157/154	L	1076	312	18.0	9.00	4125	3750	900



## CL269




- Shoulder lugs for more traction and center ribs are for stable handing.
- Tough belt for smooth wear and longer mileage.
- Special tread compound for high resistance tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.5	9.00	3550	3250	930



## CL288+




- Three main grooves and two block type ribs on the tread center provide good traction on wet and dry road conditions.
- Special anti-cut tread compound provides high resistance for cut and chipping.
- Tough belt construction for smooth tread wear.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
12.00R24	TT	20	160/157	K	1226	315	16.0	8.50	4500	4125	900



## CL366




- ◎ Wide tread design to extend tire service life.
- ◎ Low rolling resistance and excellent heat dispersion performance.
- ◎ Wide shoulder provide excellent road holding.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
13R22.5	TL	18	154/151	L	1136	320	18.0	9.75	3750	3450	830
12.00R20	TT	20	156/153	J	1125	315	18.0	8.50	4000	3650	900



## CL295




- ◎ Added more gripping power.
- ◎ Tough belt construction for smooth tread wear.
- ◎ Special compound for more mileage and cut protection.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
385/65R22.5	TL	20	160	K	1072	389	16.0	11.75	4500	/	900



## CL395




- ◎ Added more gripping power.
- ◎ Tough belt construction for smooth tread wear.
- ◎ Special compound for more mileage and cut protection.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
385/65R22.5	TL	20	160	K	1066	389	16.0	11.75	4500	/	900



## CL359



- ◎ For Wide Single Trailer.
- ◎ Tough belt construction for smooth tread wear.
- ◎ Special compound for more mileage and cut protection.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
425/65R22.5	TL	20	165	K	1120	424	18.5	13.0	5150	/	830



## CL328



- Special tread design for high traction on wet and muddy road.
- Tough belt construction for smooth tread wear and longer mileage.
- Special tread compound for high resistant tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
10.00R20	TT	18	149/146	K	1065	278	20.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1096	293	21.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1136	315	21.5	8.5	3750	3450	830
11R22.5	TL	16	146/143	L	1065	279	19.5	8.25	3000	2725	830
13R22.5	TL	18	154/151	L	1136	320	21.5	9.75	3750	3450	830
295/80R22.5	TL	18	152/149	L	1050	298	22.0	9.00	3550	3250	900



## CL338



- Special tread design for high traction on wet and muddy road.
- Tough belt construction for smooth tread wear and longer mileage.
- Special tread compound for high resistant tread cut.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
11.00R20	TT	18	152/149	F	1096	293	22.0	8.00	3550	3250	900
12.00R20	TT	20	156/153	F	1136	315	23.0	8.50	3750	3450	830



## CL388



- Wide tread and revised land/sea ratio given more mileage.
- Open groove on the shoulder given good heat dispersion performance.
- Special compound provide excellent service life and cut resistance.

Size	Type	PR	L.I.	S.S.	O.D. (mm)	S.W. (mm)	T.D. (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kpa)
									Single	Dual	
7.00R16LT	TT	14	118/114	L	785	200	20.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	K	819	215	20.0	6.00G	1500	1320	770
8.25R16LT	TT	16	128/124	K	864	235	21.0	6.50H	1800	1600	770
8.25R20	TT	16	139/137	K	986	236	21.0	6.5	2430	2300	930
9.00R20	TT	16	144/142	K	1030	259	22.0	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1065	278	23.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	J	1096	293	23.5	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1136	315	24.0	8.5	3750	3450	830



## **VOLGA TIRE GROUP**

Volga Tire & Automotive Group., Ltd, established in 2000 is an integrative group combined with the tires marketing in domestic and overseas.

The group maintains "Continuously Creating Great Service Value" in the business, takes orders of "Quality

First, Consumers First" has been ranked top class among well-known tire exporter.

VOLGA Tire Group have good cooperation with well known scientific institution to develop quality products.

Currently, VOLGA Tire Group exports over 200 sizes on TBR, OTR, LTR, TBB, LTB, AGR and INS tires.

Quality always come first for VOLGA Tire Group . Our products are already passed on many international certificates, ISO9001 , USA DOT, ECE, INMETRO, SNI, CCC, ISO10012 and more.

Our world class products help the group to win good reputation in the all over the world and highly accepted by our customers in the world.

VOLGA Tire Group will keep company's philosophy "To Satisfy the Customers" and will keep continuous efforts on developing and supplying high quality products to our customers all over the world.



[www.volgatire.com](http://www.volgatire.com)  
Ankara, Turkey  
+90 532 3453584 / +90 531 0132775  
[info@volgatire.com](mailto:info@volgatire.com)

Authorized Distributor: